VESPA GTV 300 HPE ABS – TECHNICAL SPECIFICATIONS

TYPE	HPE 4-stroke, liquid-cooled, single-cylinder, SOHC, 4-valve
DISPLACEMENT	278 cc
BORE X STROKE	75 mm × 63 mm
MAX POWER	23.8 HP (17.5 kW) @ 8,250 rpm
MAX TORQUE	26 Nm @ 5,250 rpm
FUEL SYSTEM	Electronic Fuel Injection (EFI)
CLUTCH	Automatic continuously variable transmission clutch
TRANSMISSION	CVT automatic transmission
LOAD BEARING STRUCTURE	Steel monocoque body
FRONT SUSPENSION	Single-sided link arm hydraulic suspension
REAR SUSPENSION	Twin shock absorbers with 4-position spring preload adjustment
FRONT BRAKE	Hydraulic Ø220 mm stainless steel disc, ABS
REAR BRAKE	Hydraulic Ø220 mm stainless steel disc, ABS
FRONT TYRE	120/70-12"
REAR TYRE	130/70-12"
FUEL TANK CAPACITY	8.5 litres
LENGTH/WIDTH/WHEELBASE	1,975 mm / 765 mm / 1,380 mm
SEAT HEIGHT	790 mm
KERB WEIGHT	163 kg